

**NAME**

fc-query – query font files

**SYNOPSIS**

**fc-query** [ **-Vh** ]

[ [ **-b** ] [ **--ignore-blanks** ] ] [ [ **-i** *index* ] [ **--index** *index* ] ] [ [ **-f** *format* ] [ **--format** *format* ] ] [ **--version** ] [ **--help** ] *font-file...*

**DESCRIPTION**

**fc-query** queries *font-file*(s) using the normal fontconfig rules and prints out font pattern for each face found. If **--index** is given, only one face of each file is queried, otherwise all faces are queried.

**OPTIONS**

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

- b** Ignore blanks to compute languages
- i** Only query face indexed *index* of each file.
- f** Format output according to the format specifier *format*.
- V** Show version of the program and exit.
- h** Show summary of options.

*font-file*

Query *font-file* for font faces.

**RETURN CODES**

**fc-query** returns error code 0 for successful parsing, or 1 if any errors occurred or if at least one font face could not be opened.

**SEE ALSO**

**fc-scan**(1) **FcFreeTypeQuery**(3) **FcPatternFormat**(3) **fc-cat**(1) **fc-cache**(1) **fc-list**(1) **fc-match**(1) **fc-pattern**(1)

The fontconfig user's guide, in HTML format: */usr/share/doc/fontconfig/fontconfig-user.html*.

**AUTHOR**

This manual page was updated by Behdad Esfahbod <behdad@behdad.org>.